

Standex

KOFU

High Quality Reed Switches

Reed Switch Product Line

Miniature Reed Switches

ORD213

ORD211

ORD219

Standard Reed Switches

ORD221

ORD324

ORD324H

ORD624

ORD9215

High Power Reed Switches

ORD229

ORD2210

ORD2210V

Lamp Load Reed Switches

ORD2211

ORD2211H

Long Life Reed Switches

ORD228VL

ORD311

ORD312

SPDT Transfer Reed Switches


ORT551

ORT551-1

Surface Mount

MK24

Custom Lead Forming



UL File No. E70063

ISO9001 & ISO14001 Certified

Reed-Rex LLC
4769 E. Wesley Drive
Anaheim, CA 92807
sales@reed-rex.com
(714) 970-2144

REED REX

sales@reed-rex.com • www.reed-rex.com

REED SWITCH DATA SHEET

ORD219




Miniature High Performance OKI Reed

ORD219 is a 12mm miniature single contact hermetically sealed reed switch for loads less than 100 Volts. Pull-in 10-40 AT, Drop-out minimum 5 AT. Contact rated for 1.0 Volt Amps with Rhodium (Rh) contacts engineered for long life. Low contact resistance (CR) less than 200mΩ.

Can switch or carry as low as 10 nano-Volts (10^{-9} Volts) without signal loss. Can switch or carry as low as 1 femto-Amp (10^{-15} Amps) without signal loss. Electrostatic Capacitance is less than 0.4 pF. Consumes no power in open position. Insulation Resistance is above 1 giga-ohm ($10^9 \Omega$).

Operation Temperatures: -55°C (-67°F) to $+100^{\circ}\text{C}$ (212°F). Tolerant of harsh environments including salt spray, water, humidity, gaseous & chemical fumes, oil, fuel, and dust-laden atmospheres. Shock resistant above 20Gs.



| Parameter | Specification | Unit of Measure |
|------------------------------|----------------------|-------------------|
| Pull In Value (PI) | 10-40 | Ampere Turns (AT) |
| Drop Out Value (DO) | 5 minimum | Ampere Turns (AT) |
| Contact Resistance | 100 maximum | Milliohms (mΩ) |
| Breakdown Voltage | 200 minimum | Volts DC (VDC) |
| Insulation Resistance | 10^9 minimum | Ohms (Ω) |
| Electrostatic Capacitance | 0.3 maximum | Picofarads (pF) |
| Contact Rating | 10 | Volt-ampere (VA) |
| Max Switching Voltage | 100 DC / 100 AC | Volts (V) |
| Max Switching Current | 0.5 | Amps (A) |
| Max Carry Current | 1.0 | Amps (A) |
| Response Time | 0.4 maximum | Milliseconds (ms) |
| Bounce Time | 0.3 maximum | Milliseconds (ms) |
| Release Time | 0.05 maximum | Milliseconds (ms) |
| Resonant Frequency | 5,900 +/-400 | Hertz (Hz) |
| Max Operating Frequency | 500 | Hertz (Hz) |
| Minimum Expected Switch Life | 100 million switches | 5 VDC @ 1mA |

For Additional Specifications, www.reed-rex.com/okireedswitchdatabook