

Standex

KOFU

High Quality Reed Switches

Reed Switch Product Line

Miniature Reed Switches

ORD213

ORD211

ORD611

ORD219

Standard Reed Switches

ORD221

ORD324

ORD324H

ORD624

ORD9215

High Power Reed Switches

ORD229

ORD2210

ORD2210V

Lamp Load Reed Switches

ORD2211

ORD2211H

Long Life Reed Switches

ORD228VL

ORD311

ORD312

SPDT Transfer Reed Switches


ORT551

ORT551-1

Surface Mount

MK24

Custom Lead Forming



UL File No. E70063

ISO9001 & ISO14001 Certified

Reed-Rex LLC
4769 E. Wesley Drive
Anaheim, CA 92807
sales@reed-rex.com
(714) 970-2144

REED REX

sales@reed-rex.com • www.reed-rex.com

REED SWITCH DATA SHEET


ORD611



Ultra Miniature OKI Reed Switch

ORD611 is a 10mm ultra miniature single contact hermetically sealed reed switch for loads less than 200 Volts. Pull-in 8-40 AT, Drop-out minimum 2 AT. Contact rated for 10 Volt Amps with Rhodium (Rh) contacts engineered for long life. Low contact resistance (CR) of 120mΩ max. Max carry current is .5 amps. Electrostatic Capacitance is less than 0.18 pF. Consumes no power in open position. Insulation Resistance is above 1 giga-ohm (10⁹ Ω).

Operation Temperatures: -55°C (-67°F) to +100°C (212°F). Tolerant of harsh environments including salt spray, water, humidity, gaseous & chemical fumes, oil, fuel, and dust-laden atmospheres. Shock resistant above 20Gs.



Parameter	Specification	Unit of Measure
Pull In Value (PI)	8-40	Ampere Turns (AT)
Drop Out Value (DO)	2 minimum	Ampere Turns (AT)
Contact Resistance	125 maximum	Milliohms (mΩ)
Breakdown Voltage	250 minimum	Volts DC (VDC)
Insulation Resistance	10 ⁹ minimum	Ohms (Ω)
Electrostatic Capacitance	0.18 maximum	Picofarads (pF)
Contact Rating	10	Watts / Volt Amps
Max Switching Voltage	200 DC / 150 AC	Volts (V)
Max Switching Current	0.3	Amps (A)
Max Carry Current	0.5	Amps (A)
Response Time	0.3 maximum	Milliseconds (ms)
Bounce Time	0.3 maximum	Milliseconds (ms)
Release Time	0.05 maximum	Milliseconds (ms)
Resonant Frequency	7,500 +/-500	Hertz (Hz)
Max Operating Frequency	500	Hertz (Hz)
Minimum Expected Switch Life	300 million switches	5 VDC @ 1mA

For Additional Specifications, www.reed-rex.com/okireedswitchdatabook